

PRODUCT FUNCTION

- Used for measuring resistance of cables and wires; the contact resistance of switches, connectors and relays; the resistance of metal riveting; the winding resistance of coils, motors and transformers; the connection resistance between metal components; the resistance of welding points; the resistance of parallel connection of batteries; the measurement of wire length, etc.

PRODUCT FEATURES

- The maximum test current is 10A, with a wide measurement range of 1.0uΩ to 2500Ω and a high resolution of 0.1uΩ.
- Two measurement modes are available: automatic measurement mode, which automatically selects the test current based on the load; and manual measurement mode, which offers five test current settings: 10A, 1A, 100mA, 10mA, and 1mA.
- With 5-inch true-color LCD touch screen, allowing for operation via touch or buttons.
- With 75°C resistance conversion function, compensating for the temperature and material of the test sample.
- With alarm functions, automatic shutdown, Bluetooth communication, and a USB interface.



TECHNICAL SPECIFICATION

Power Supply	DC14.8V 5200mAh rechargeable lithium battery		
LCD Dimension	5-inch full-color LCD touch panel with a resolution of 480 x 854 pixels		
Measurement Mode	Automatic & Manual		
Display Range	1.0uΩ ~ 2500.0Ω		
Range & Test Current	1.0uΩ ~ 2500.0Ω	AUTO	
	0.0010mΩ ~ 249.99mΩ	10A	± 0.2 % ± 2uΩ
	250.0mΩ ~ 2.4999	1A	± 0.2 % ± 3mΩ
	250.0mΩ ~ 2.4999Ω	100mA	± 0.2 % ± 30mΩ
	25.00Ω ~ 249.00Ω	10mA	± 0.2 % ± 300mΩ
Max Resolution	250.0Ω ~ 2500.0Ω	1mA	± 0.2 % ± 3Ω
	0.1uΩ		
Measurement Accuracy	± 0.2 % ± 2uΩ		
Test Current Gear	AUTO,10A,1A,100mA,10mA,1mA		
Output Voltage	4.2V MAX		
Alarm Setting	Alarm critical value setting range; 1mΩ ~ 30Ω, 0Ω is not start the alarm function		
Alarm Warning	When the test value exceeds the alarm setting value,warning flashes to give a prompt		
Clock function	24-hour format, showing hours, minutes and seconds		
Data Storage	1000 groups (data will not be lost after power failure or battery replacement)		
Automatic Shutdown	After setting automatic shutdown, 15 minutes without any operation after starting up will automatic shutdown		
Bluetooth Communication	Yes		



Guangdong ETCR Electronic Technology Co.,Ltd

10th F, U-5, Liandong Intelligent Manufacture Park,
No. 105, Shilong N. Road, Nanhai, Foshan, China

Tel: (86-757)66860936
info@etcr.net
www.etcrmeter.com

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.

ETCR METER[®]

GUANGDONG ETCR ELECTRONIC TECHNOLOGY CO.,LTD.

USB Interface	With USB interface, software monitoring, storage data can be uploaded to computer, save and print.
Withstand Voltage	AC 3700V/rms (between the housing and screws)
Host Dimension	280mm x 260mm x 160mm
Weight	Approx. 6.6kg (include all accessories)
Accessories	Tester*1PC; Test line*2PCS; USB communication cable*1PC; Special charger*1PC; Tool bag*1PC

Guangdong ETCR Electronic Technology Co.,Ltd

10th F, U-5, Liandong Intelligent Manufacture Park,
No. 105, Shilong N. Road, Nanhai, Foshan, China

Tel: (86-757)66860936
info@etcrcr.net
www.etcrcr.com

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.