

PRODUCT FUNCTION

- Measurement of AC leakage current, AC current.

PRODUCT FEATURES

- The iron core is made with high performance material and digital integration technology, small volume, high accuracy.
- Adopts magnetic shielding technology, almost unaffected by the external magnetic field, strong anti-interference ability.
- Peak hold function. Data storage function.



TECHNICAL SPECIFICATION

Power Supply	DC3V Alkaline dry battery LR03*2PCS
LCD Size	35mm x 21.5mm; display area: 32mm x 15mm
Range	0.000mA ~ 60.0A
Resolution	1uA
Measurement Accuracy	± 1.5 % rdg ± 5dgt (23°C ± 3°C, below 70 % RH)
CT Size	25 x 30mm
Sampling Rate	2 times/sec
Frequency	50Hz, 60Hz Automatic identification
Data Store	99 groups , flash display "FULL" symbol indicate stored full
Peak Hold	Peak capture and hold function, long press HOLD button display peak value
Data Hold	Data hold function: "DH" symbol display
Overflow Display	Exceed measure range overflow function: "OL" symbol display
Automatic Shut Down	5 Minutes after power on, will shut down automatically without any operation to reduce the power consumption.
Battery Voltage	When battery voltage lower than 2.8V, will display low battery voltage symbol "⚡", remind to replace battery
Working Current	5mA
Line Voltage	Below AC 600V circuit measurement
Shift	Automatically
Meter Weight	0.32kg (include accessories)
Meter Dimension	172mm x 71mm x 32mm
Accessories	Meter*1PC; Tool bag*1PC; LR03 Alkaline battery*2PCS

Guangdong ETCR Electronic Technology Co.,Ltd

10th F, U-5, Liandong Intelligent Manufacture Park,
No. 105, Shilong N. Road, Nanhai, Foshan, China

Tel: (86-757)66860936
info@etcrcr.net
www.etcrcr.com

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.