

PRODUCT FUNCTION



- AC current, AC voltage, DC current, resistance, on-off test, etc.

PRODUCT FEATURES

- Flexible coil without any exposed metal conductor, non-contact type measurement, safe and reliable. Small size, light weight, soft and flexible, suitable for narrow environment and cable densely places, as well as measuring conductor current with large size or irregular shape .
- Coil size: $\Phi 150\text{mm}$. Customizable dimensions can be provided according to user requirements.
- Can be used as a regular multimeter.



TECHNICAL SPECIFICATION

Power Supply	DC 4.5V Alkaline dry battery (LR03 1.5V x 3PCS)		
LCD Size	43mm x 38mm; Display domain: 36.5mm x 29mm		
Test Method	True effective value		
AC Current Measurement	Range: AC 0mA ~ 9999A	Accuracy: $\pm 2\% \text{rdg} \pm 15 \text{dgt}$	Resolution: 1mA
AC Voltage Measurement	Range: AC 0.1V ~ 750V	Accuracy: $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$	Resolution: 0.1V
DC Voltage Measurement	Range: DC 0.1V ~ 1000V	Accuracy: $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$	Resolution: 0.1V
Resistance Measurement	Range: $0\Omega \sim 2000\Omega$	Accuracy: $\pm 2\% \text{rdg} \pm 5 \text{dgt}$	Resolution: 1Ω
Coil Inner Diameter	$\Phi 150\text{mm}$		
Data Storage	600 groups		
Measured Current Frequency	50Hz / 60Hz(Automatic identify)		
Sampling Rate	1 time/s		
Backlight	with backlight,  button control		
Data Hold	Data hold function: "HOLD" symbol display		
Overflow Display	Exceed measure range overflow function: "OL" symbol display		
Automatic Shutdown	After being powered on for about 10 minutes without any operation, the instrument will automatically shut down to reduce battery consumption.		
Battery Voltage	While battery voltage is lower than 3.8V. low battery voltage symbol "  "display, remind to replace the battery		
Working Current	Backlight power on: 80mA; Backlight off: 40mA		
Working environment	- 10°C ~ 40°C; below 80% RH		
Store environment	- 10°C ~ 60°C; below 70% RH		
Insulation Strength	AC 3700V/rms (between the core and the casing)		
Suitable Safety Standard	IEC1010-1, IEC1010-2-032, Pollution 2, CAT IV(600V) ,IEC61326(EMC standard)		
Meter Size	165mm x 105mm x 35mm		

Guangdong ETCR Electronic Technology Co.,Ltd

10th F, U-S, Liandong Intelligent Manufacture Park,
No. 105, Shilong N. Road, Nanhai, Foshan, China

Tel: (86-757)66860936
info@etcr.net
www.etcrmeter.com

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.

ETCR METER[®]

GUANGDONG ETCR ELECTRONIC TECHNOLOGY CO.,LTD.

Weight	0.65kg (include accessories)
Accessories	Meter*1PC; Test pen leads*2PCS (1 red and 1 black); LR03 batteries*3PCS; Tool bag*1PC

Guangdong ETCR Electronic Technology Co.,Ltd

10th F, U-5, Liandong Intelligent Manufacture Park,
No. 105, Shilong N. Road, Nanhai, Foshan, China

Tel: (86-757)66860936
info@etc.net
www.etcrcr.com

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.